



CA-CCL-60

Item Number 4493622

Premium charging hose with ball valve. The special rubber compound is extremely durable due to its high pressure resistance and low embrittlement. Equipped with full flow ball valve to help eliminating the chance of refrigerant burns or atmospheric releases.

- Replaceable long life neoprene seal
- 870 psi working pressure
- High quality rubber compound for high elasticity, against hardening and embrittlement

Technical Data

| | |
|-----------------------------|---|
| Material | Brass Rubber |
| Color | blue red yellow |
| Number of Hoses | 3 |
| Length | 60 " |
| Sealing | Neoprene |
| System Connection | 1/4" SAE 45° bend With core depressor |
| Device connection | 1/4" SAE |
| Valve Core Depressor | Yes |
| Ball Valve | Yes |
| Working Pressure | 870 psi |
| Burst Pressure | 3,600 psi |
| Diameter | 1/4" |
| Packaging | Blister |

Accessories

Acknowledged globally



| | | |
|---------|-------------------|--|
| 4661147 | CA-5/16"SAE-Y | Ball valve, yellow, 5/16"SAE X 5/16"SAE |
| 4661121 | CA-5/16"SAE-B | Ball valve, blue, 5/16"SAE X 5/16"SAE |
| 4661139 | CA-5/16"SAE-R | Ball valve, red, 5/16"SAE X 5/16"SAE |
| 4682446 | CA-5/16"SAE-Y-45° | Ball valve for charging hose, yellow with threaded hull 45° bent |
| 4682420 | CA-5/16"SAE-B-45° | Ball valve, blue with threaded hull 45° bent |
| 4682438 | CA-5/16"SAE-R-45° | Ball valve for charging hose, red with threaded hull 45° bent |

Spare Parts

| | | |
|---------|-------------|---------------------------------|
| 9880871 | P-509-T/10 | PTFE gasket 1/4" SAE, 10 pieces |
| 9883979 | P-509-T/100 | PTFE gaskets, 100 pieces |
| 9880869 | P-513/10 | Core depressor 1/4", 10 pieces |
| 9883961 | P-513/100 | Core depressor 1/4", 100 pieces |