



STARTEK-C

Item Number

4660664

Leak detector for combustible gases

Replaced by **TRITECTOR-RCT**

- Detects flammable refrigerants (R290, R600, R600a, ...)
- Easy handling thanks to one-button operation
- Sensitivity levels selectable with double click
- Automatic recalibration
- Leakage is indicated by optical and acoustic signals
- Auto-Shutoff
- In a practical holster with belt clip
- In a sturdy plastic case

Technical Data

Color	red yellow (RAL 1023)
Standards	EN 61326-1:2013 EN 55011 :2018-05 EN 61000-4-2 :2009-12 EN 61000-4-3 :2011-04 EN 50581:2012
RoHS Conformity	1
RoHS Conformity	Yes
Refrigerant(s)	R290 R600 R600a more
Operating Temperature Range	34 - 122 °F
Battery	2 x AA
Operating Hours	11 h
Functions	2 sensitivity levels, Audible and visual alarm,

Acknowledged globally



	Auto shut-off, Battery life indicator, Belt clip
Sensitivity	< 50 ppm
Refrigerant Type	Combustible gases
Measurement Technology	electrical
Tube Length	12 "
Scope of Supply	Batteries Case Instruction manual
Packaging	Sturdy plastic case
Warm-up Time	45 s

Spare Parts

4660672	ES-C	Replacement sensor for STARTEK-C
---------	------	----------------------------------