Acknowledged globally



CA-CL-9-B-M

Item Number 4682056

Premium charging hose with ball valve. The special rubber compound is extremely durable due to its high pressure resistance and low embrittlement. Equipped with full flow ball valve to help eliminating the chance of refrigerant burns or atmospheric releases.

- Replaceable long life neoprene seal
- 870 psi working pressure
- High quality rubber compound for high elasticity, against hardening and embrittlement

Technical Data

Material	Brass | Rubber
Color	blue
Number of Hoses	1
Length	9 "
Sealing	Neoprene
System Connection	1/4" SAE | 45° bend | With core depressor
Device connection	1/4" SAE
Valve Core Depressor	Yes
Ball Valve	Yes
Working Pressure	870 psi
Burst Pressure	3,600 psi
Diameter	1/4"
Packaging	Blister

Spare Parts

REFCO Manufacturing (US) Inc.
66 B Industry Avenue
Springfield MA 01104

Phone 413 739 4761
sales@refcoswiss.com

Certificate
ISO 9001 / ISO 14001

9880872	P-509/10	Neoprene gasket, 1/4" SAE, 10 pieces
9880871	P-509-T/10	PTFE gasket 1/4" SAE, 10 pieces
9883980	P-509/100	Neoprene gaskets, 100 pieces
9883979	P-509-T/100	PTFE gaskets, 100 pieces

REFCO Manufacturing (US) Inc.
66 B Industry Avenue
Springfield MA 01104

Phone 413 739 4761
sales@refcoswiss.com