Acknowledged globally





TRACE-LOCATOR

Item Number 4686715

The leak detector for tracer gas 95/5 (95% nitrogen, 5% hydrogen). The gas escapes at the leak and can be easily located with the TRACE-LOCATOR. Due to the low density of hydrogen, which is lighter than air, even the smallest leaks can be detected quickly. The large LCD display always shows the most current data by means of a colored pie chart. The TRACE-LOCATOR is delivered in a practical, sturdy plastic case.

Replaced by TRITECTOR-RCT

- High sensitivity to environmentally friendly hydrogen mixtures
- Equipped with three UV and three LED lamps each

Technical Data

Material	ABS TPU FR-4		
Color	yellow (RAL 1023)		
Standards	EN35422 SAE-J2970		
RoHS Conformity	1		
RoHS Conformity	Yes		
Refrigerant(s)	Tracer Gas		
Operating Temperature Range	24 - 125 °F		
Ingression Protection	IP54		
Battery	4 x AA		
Operating Hours	4 h		
Functions	3-level sensitivity, Ambient concentration reset, Mute function, Low battery indication,		

Acknowledged globally



	UV-light and LED, Auto power off	
Sensitivity	< 5 ppm N2/H2	
Refrigerant Type	Tracer Gas	
Measurement Technology	electrical	
Sensor Lifetime	1000 h	
Tube Length	17 "	
Warm-up Time	30 s	

Spare Parts

4686823	TRACE-LOCATOR- SEN-01	Replacement sensor for TRACE-LOCATOR
4686821	LOCATOR- FILTER/5	Spare filter, 5 pieces
4687034	LOCATOR-LED- UV/6	Spare LED UV for leak detector, 6 pcs.
4686828	LOCATOR-LED- WHITE/6	spare LED white for leak detector, 6 pcs.
4686703	TRACE-LOCATOR- TV-01	Test vial for TRACE-LOCATOR
4686708	TRACE-LOCATOR- CASE	Case for leak detector