Acknowledged globally



TAP-DOUBLE-SET

Item Number 4687789

The new wireless digital temperature and pressure gauge set is a user-friendly instrument that measures temperature and pressure (high and low pressure side) of air conditioning and refrigeration systems.

- Fast and easy connection to pressure source and temperature measuring point
- The cordless K-type temperature clamps are suitable for pipe diameters from 1/4" to 1 5/8"
- Measurement and calculation of superheat and subcooling can be displayed on the device display as well as on the mobile phone
- Up to 6 TAP devices can be monitored simultaneously on the mobile phone
- Create report on Smart Phone and simply send it via e-mail to the office
- Operation with AAA batteries
- In a sturdy plastic case, as double set

For Android Users: The App is not supported on Google Play store. You still can use the App as follows. Download the App here, unzip the zip file and run the .apk on your Android OS.

Technical Data

Material	Brass | ABS | TPE
Color	yellow (RAL 1023) | green (RAL 6026)
RoHS Conformity	1
RoHS Conformity	Yes
Refrigerant(s)	R11 | R113 | R114 | R12 | R123 | R124 | R13 | R134a | R13B1 | R22 | R227ea | R23 | R290 | R32 | R401A | R401B | R402A | R402B | R403B | R404A | R406A | R407A | R407B | R407C | R407F | R408A | R409A | R410A | R413A | R414B | R416A | R417A | R420A | R422A | R422B | R422C | R422D | R427A | R437A | R438A | R448A | R449A | R450A | R452A | R500 | R502 | R503 | R507 | R508A | R508B | R513A | R600a | R744 | R1233zd | R1234yf | R1234ze

REFCO Manufacturing (US) Inc.
66 B Industry Avenue
Springfield MA 01104

Phone 413 739 4761
sales@refcoswiss.com

Certificate
ISO 9001 / ISO 14001

Accuracy Class	1.0 (+/-1% FS)
Gas Connection	1/4" SAE
Pressure Scale	bar | psi | kPa | MPa
Operating Temperature Range	32 - 122°F
Storage Temperature Range	-4 - 140°F
Pressure Range	-14 - 870 psi
Resolution	0.07 bar, 0.1 psi, 7 kPa, 0.007 MPa
Battery	4 x AAA | 2 x 3 AAA
Operating Hours	40h / 50h
Signal Range	100 ft
Functions	Superheat / Subcool, Pressure zeroing, Refrigerant favorites Auto off Unit and language settings, Update refrigerants, Calibration of WIRELESS-CLAMP WTC and TAP pressure gauge, Wireless connections
Packaging	Sturdy plastic case
Sensor type	K-type | Piezo Sensor
Temperature measuring range	-40 - 257 °F
Temperature Units	°C | °F
Temperature Accuracy	+/-1 K
Temperature Resolution	0.1 °C / 0.1 °F
Scope of Supply	2 TAP Pressure Gauge, 2 WIRELESS-CLAMP WTC, 2 SAE ¼" female/female adapter, 1 USB Cable, 14 Batteries, 1 Manual, 1 Case

Accessories

9881265	CL-6-R	Charging hose, red, 1/4" SAE, 6"/15 cm 1x straight 1/4" SAE, 1x bended 1/4" SAE with core depressor
9881256	CL-6-B	Charging hose, blue, 1/4" SAE, 6"/15 cm 1x straight 1/4" SAE, 1x bended 1/4" SAE with core depressor
4687824	QC-S4A-5/16"SAE/2	Quick coupler straight 1/4" SAE x 5/16"SAE, 2 pcs.

REFCO Manufacturing (US) Inc.
66 B Industry Avenue
Springfield MA 01104

Phone 413 739 4761
sales@refcoswiss.com

Certificate
ISO 9001 / ISO 14001

4687631	SWIVEL-ARM-1/4"SAE-N	Swivel arm for vacuum gauge, 1/4" SAE
4687854	A-31851-TAP	Threaded T style 1/4 "SAE x 1/4 "SAE x 1/4 "SAE
4687095	QC-S410A/2	Adapter with core depressor 1/4" SAE x 5/16"SAE, 2 pieces

Spare Parts

4687787	TAP	Pressure Gauge
4687785	WIRELESS-CLAMP WTC	Temperature clamp for REFMATE and TAP
4687823	QC-S4A-1/4"SAE/2	Quick coupler straight 2 x 1/4" SAE, 2 pieces
4687793	TAP-MARKING-RING-SET	Marking rings for TAP and WIRELESS-CLAMP-WTC 4x2 pcs per size, blue and red
4687859	TAP-DOUBLE-SET-CASE	Case for TAP-DOUBLE-SET