Acknowledged globally



HCL6-60-Y

Item Number 9881313

The larger inner diameter allows a higher volume flow during evacuation and filling. This reduces valuable working time.

- High volume flow rate due to larger diameter
- Knurled brass nut for easy finger tightening
- High quality material for maximum durability, against hardening and embrittlement
- Eight sided crimp to ensure maximum hose life

Technical Data

Material	Brass | Rubber
Color	yellow
Number of Hoses	1
Length	60 "
Sealing	Neoprene
System Connection	3/8" SAE | Straight
Device connection	3/8" SAE
Valve Core Depressor	No
Ball Valve	No
Working Pressure	465 psi
Burst Pressure	2,250 psi
Diameter	3/8"
Packaging	Blister

Spare Parts

REFCO Manufacturing (US) Inc.
66 B Industry Avenue
Springfield MA 01104

Phone 413 739 4761
sales@refcoswiss.com

Certificate
ISO 9001 / ISO 14001

9880870	P-510/10	Neoprene O-rings 3/8" SAE, 10 pieces
9884813	A-40513/10	Core depressors 3/8", 10 pieces

REFCO Manufacturing (US) Inc.
66 B Industry Avenue
Springfield MA 01104

Phone 413 739 4761
sales@refcoswiss.com