Acknowledged globally



CCL-60-J2888

Item Number 9884729

Environmentally friendly charging hoses with special barrier protection. The special rubber compound is extremely durable due to its high pressure resistance and low embrittlement. Made from special material which prevents virtually any permeation of refrigerant, yet remain felxible and easy to work with. Meets SAE J2196 and SAE J2888 for permeation allowance.

- Tested according to SAE J2196 and J2888
- Replaceable neoprene seal
- High quality material for maximum service life, against hardening and embrittlement
- Serrated union nuts for better grip when tightening by hand

Technical Data

Material	Brass | Rubber
Color	blue | red | yellow
Number of Hoses	3
Length	60 "
Sealing	Neoprene
System Connection	1/4" SAE | 45° bend | With core depressor
Device connection	1/4" SAE
Valve Core Depressor	Yes
Ball Valve	No
Working Pressure	870 psi
Burst Pressure	3,600 psi
Standards	SAE J2196 SAE J2888
Diameter	1/4"

REFCO Manufacturing (US) Inc.
66 B Industry Avenue
Springfield MA 01104

Phone 413 739 4761
sales@refcoswiss.com

Certificate
ISO 9001 / ISO 14001

Packaging	Blister

Accessories

4661147	CA-5/16"SAE-Y	Ball valve, yellow, 5/16"SAE X 5/16"SAE
4661121	CA-5/16"SAE-B	Ball valve, blue, 5/16"SAE X 5/16"SAE
4661139	CA-5/16"SAE-R	Ball valve, red, 5/16"SAE X 5/16"SAE
4682446	CA-5/16"SAE-Y-45°	Ball valve for charging hose, yellow with threaded hull 45° bent
4682420	CA-5/16"SAE-B-45°	Ball valve, blue with threaded hull 45° bent
4682438	CA-5/16"SAE-R-45°	Ball valve for charging hose, red with threaded hull 45° bent

Spare Parts

9880871	P-509-T/10	PTFE gasket 1/4" SAE, 10 pieces
9883979	P-509-T/100	PTFE gaskets, 100 pieces
9880869	P-513/10	Core depressor 1/4", 10 pieces
9883961	P-513/100	Core depressor 1/4", 100 pieces

REFCO Manufacturing (US) Inc.
66 B Industry Avenue
Springfield MA 01104

Phone 413 739 4761
sales@refcoswiss.com