



TRITECTOR-RC

Item Number 4688683

The TRITECTOR™ is the practical 3-in-1 solution for the professional refrigeration engineer – with easily replaceable sensors, all common refrigerants, combustible gases and tracer gases can be detected with only one device. The adjustable sensitivity levels find even the smallest leaks, and the ambient concentration is continuously compensated automatically or can also be compensated manually. As soon as a leak is detected, the color LCD display gives a visual signal and an optional sound is emitted. As with other REFCO products, either AA batteries or Micro-USB supplies power - making annoying delays caused by dead batteries a thing of the past.

This item has two sensors only - for refrigerants and for flammable refrigerants.

- Intuitive handling
- Intelligent electronics that automatically detect the connected sensor
- Exchangeable sensors for refrigerants, combustible gases and tracer gases
- Variable power supply (batteries & USB)
- Automatic and manual reset of the ambient concentration
- High quality LCD display

Technical Data

Material	ABS TPE
Color	yellow green
Standards	Refrigerants: EN-14624:2012, SAE J1627, SAE J2791, SAE J2913 Combustibles: BS 7348
RoHS Conformity	Yes
Operating Temperature Range	+14 °F to +122 °F
Storage Temperature Range	-4 °F to +140 °F
Humidity Range	0 - 90 % relative humidity (no condensation)

Ingression Protection	IP41
Battery	4 x AA
Operating Hours	12 h
Functions	<p>Sensor exchange</p> <p>Ambient concentration reset:</p> <ul style="list-style-type: none"> - automatic - manual <p>Peak = peak function indicates maximum measured value</p> <p>Auto shut off</p> <p>Sensitivity Level:</p> <ul style="list-style-type: none"> - low - medium - high <p>Mute function</p>
Sensitivity	Refrigerant [R]: 0.04 oz/yr R134a Combustible gas [C]: 0.04 oz/yr R290, < 5 ppm methane
Refrigerant Type	Combustible gases HFO HCF HCFC CFC Refrigerants
Measurement Technology	Metal-oxide-semiconductor
Sensor Lifetime	10 y
Tube Length	16 "
Scope of Supply	Batteries Case Instruction manual
Packaging	Sturdy plastic case
Warm-up Time	45 s

Spare Parts

4688370	R-SENSOR	Refrigerant sensor
4688371	C-SENSOR	Combustible gas sensor
4688372	T-SENSOR	Tracer gas sensor
4688367	TRITECTOR-FILTER/5	Replacement filter for TRITECTOR, 5 pieces
4688364	TRITECTOR-CASE	Case