## Acknowledged globally





### **REFCLAMP-SET**

#### **Item Number** 4688733

The REFCLAMP measures both the tube and air temperature as well as the humidity in the ambient air of mobile and stationary refrigeration systems and heat pumps.

It has two sensors included: a pipe temperature sensor and a humidity sensor. Furthermore, the outside temperature can be measured by means of a plug-in K-type sensor.

The illuminated display guarantees constant control of the measured values. Another plus: The narrow tip also enables measurement in hard-to-reach places.

Furthermore, the clamp can be connected to REFMATE and the REFMESH app and thus contribute to an optimal adjustment of the system.

#### **Functions:**

- Target superheat
- Tube temperature and air temperature measurement
- Humidity measurement
- Calculation of wet bulb temperature
- · Calculation of superheat and subcooling
- Temperature difference calculation
- Ice water calibration

- Fast response time
- Permanent view of the measured values thanks to illuminated display
- Comfortable handling thanks to wireless connection and ergonomic design
- Simple operation with 2 buttons
- Real-time display of measured values on the clamp, the REFMATE, and the REFMESH app
- High range of 330 yards

#### **Technical Data**

# Acknowledged globally



Material         Polyamide           Color         yellow   green           Number of Pieces         2           Standards         CE FCC IC RCM RoHS REACH           ROHS Conformity         Yes           RoHS Conformity         1           Operating Temperature Range         -4 °F – 122 °C           Humidity Range         5 – 100 %
Number of Pieces  2  Standards  CE FCC IC RCM RoHS ReACH  RoHS Conformity  Yes  RoHS Conformity  1  Operating Temperature Range  -4 °F – 122 °C
Standards  CE FCC IC RCM RoHS ReACH  ROHS Conformity  Yes  ROHS Conformity  1  Operating Temperature Range  -4 °F – 122 °C
FCC IC RCM ROHS ROHS REACH  ROHS Conformity Yes  ROHS Conformity 1  Operating Temperature Range -4 °F - 122 °C
RoHS Conformity 1  Operating Temperature Range -4 °F – 122 °C
Operating Temperature Range -4 °F – 122 °C
Humidity Range 5 – 100 %
Measured Variable Temperature   Humidity
Operating Temperature Range -4 °C - 122 °C
Diameter 5 - 44 mm
Battery 2 x 2 AAA
Tube temperature and air temperature measurement Humidity measurement Wet bulb temperature calculation Ice water calibration Connection to REFMATE and REFMESH Calculation of superheat and subcooling in combination with the REFMATE Target superheat in combination with the REFMATE Temperature difference calculation - Delta T (in REFMESH) Absolute humidity (REFMESH)
Enthalpy (REFMESH)
Scope of Supply  Batteries   Quick Guide
Scope of Supply Batteries   Quick Guide
Scope of Supply  Batteries   Quick Guide  Packaging  Blister
Scope of Supply  Batteries   Quick Guide  Packaging  Blister  Accuracy  ±1°F

## Acknowledged globally



### Accessories

4681394 K-TYPE-SENSOR External temperature sensor for REFMATE and DIGIMON