Acknowledged globally



# ECO-5-A2L

**Item Number** 4688957

Two-stage vacuum pump for maximum pumping performance.

- **A2L suitable**
- Easy to start
- Free air displacement 5 cfm
- Compact design with aluminium housing and easy to grip carrying handle
- Very quiet operation
- High pumping capacity reduces evacuation time
- Both 1/4" and 3/8" SAE flare inlet connections allow for flexibility of connections
- Vacuum pump oil included

## Technical Data

| | |
|---|---|
| **Material** | Steel |
| **Color** | green (RAL 6026) \| grey (RAL 7040) \| yellow (RAL 1023) |
| **RoHS Conformity** | Yes |
| **Gas Connection** | 1/4" SAE \| 3/8" SAE |
| **Flow Rate** | 5 cfm |
| **End Vacuum** | 15 micron |
| **Voltage** | 115 VAC |
| **Frequency** | 60Hz |
| **Protection Class** | I |
| **Oil Tank Volume** | 11 oz |
| **Energy Consumption** | 0.5 HP |
| **Cable Length** | 78 " |
| **Scope of Supply** | Vacuum pump oil |
| **Packaging** | Cardboard box |

**REFCO Manufacturing (US) Inc.**
66 B Industry Avenue
Springfield MA 01104

Phone 413 739 4761
sales@refcoswiss.com

Certificate
ISO 9001 / ISO 14001

| | |
|---|---|
| **Number of Stages** | 2 |

# Accessories

| | | |
|---|---|---|
| 9882473 | 19800-SV | Vacuum gauge, ø 80 mm, 1/8" NPT with safety valve, recalibratable, scale: 1'000 - 0 mbar |
| 4495340 | DV-44 | Vacuum pump oil, 250ml viscosity 46 mm²/s at 40 °C |
| 4495331 | DV-48 | Vacuum pump oil, 5l viscosity 46 mm²/s at 40 °C |
| 4688541 | REFVAC-RC | Wireless digital vacuum gauge connection 1/4"SAE male, Units: Micron, mbar, Pa, Torr, mTorr, psi and inHg |
| 9881313 | HCL6-60-Y | Large diameter hose 3/8", yellow, 60"/150 cm 2x 3/8" SAE female |
| 9881269 | CL-60-Y | Charging hose, yellow, 1/4" SAE, 60"/150 cm 1x straight 1/4" SAE, 1x bended 1/4" SAE with core depressor |
| 4689646 | FLOW-Y | High-flow Y-splitter for rapid evacuation |

**REFCO Manufacturing (US) Inc.**
66 B Industry Avenue
Springfield MA 01104

Phone 413 739 4761
sales@refcoswiss.com