



## ECO-5-A2L

**Item Number 4688957**

Two-stage vacuum pump for maximum pumping performance.

- **A2L suitable**
- Easy to start
- Free air displacement 5 cfm
- Compact design with aluminium housing and easy to grip carrying handle
- Very quiet operation
- High pumping capacity reduces evacuation time
- Both 1/4" and 3/8" SAE flare inlet connections allow for flexibility of connections
- Vacuum pump oil included

## Technical Data

<b>Material</b>	Steel
<b>Color</b>	green (RAL 6026)   grey (RAL 7040)
<b>RoHS Conformity</b>	Yes
<b>Gas Connection</b>	1/4" SAE   3/8" SAE
<b>Flow Rate</b>	5 cfm
<b>End Vacuum</b>	15 micron
<b>Voltage</b>	115 VAC
<b>Frequency</b>	60Hz
<b>Protection Class</b>	I
<b>Oil Tank Volume</b>	10.99 oz
<b>Energy Consumption</b>	0.37 kW
<b>Cable Length</b>	78 "
<b>Scope of Supply</b>	Vacuum pump oil
<b>Packaging</b>	Cardboard box

Number of Stages 2

## Accessories

4688291	REFVAC-RC	Wireless digital vacuum gauge connection 1/4"SAE male, Units: Micron, mbar, Pa, Torr, mTorr, psi and inHg
9882473	19800-SV	Vacuum gauge, $\varnothing$ 80 mm, 1/8" NPT with safety valve, recalibratable, scale: 1'000 - 0 mbar
4495340	DV-44	Vacuum pump oil, 250ml viscosity 46 mm <sup>2</sup> /s at 40 °C
4495331	DV-48	Vacuum pump oil, 5l viscosity 46 mm <sup>2</sup> /s at 40 °C