



Acknowledged globally



ECO-9-A2L

Item Number 4689189

The two-stage vacuum pumps of the ECO series are suitable for all common refrigerants including A2L. They feature a compact aluminum housing with a sturdy handle. The high pumping capacity reduces evacuation time significantly, yet they operate very quietly.

An integrated solenoid valve prevents the loss of the already generated vacuum in case of accidental shutdown.

Additionally, the pumps come equipped with 1/4" and 3/8" SAE flare Intake port, allowing for flexible hose selection and compatibility with various systems. Moreover, they are easy to operate and maintenance-friendly.

- **A2L suitable**
- Integrated solenoid valve prevents vacuum loss during accidental shutdowns
- Easy to start
- Compact design with aluminium housing and easy to grip carrying handle
- Very quiet operation
- High pumping capacity reduces evacuation time
- Both 1/4" and 3/8" SAE flare inlet connections allow for flexibility of connections
- Vacuum pump oil included

Technical Data

Material	Steel
Color	yellow (RAL 1023) green (RAL 6026) grey (RAL 7040)
RoHS Conformity	Yes
Gas Connection	1/4" SAE 3/8" SAE
Flow Rate	9 cfm



Acknowledged globally

End Vacuum	15 micron
Voltage	115 VAC
Frequency	60Hz
Protection Class	I
Oil Tank Volume	17 oz
Energy Consumption	1 HP
Scope of Supply	Vacuum pump oil
Packaging	Cardboard box
Number of Stages	2

Accessories

4688541	REFVAC-RC	Wireless digital vacuum gauge connection 1/4"SAE male, Units: Micron, mbar, Pa, Torr, mTorr, psi and inHg
9882473	19800-SV	Vacuum gauge, ø 80 mm, 1/8" NPT with safety valve, recalibratable, scale: 1'000 - 0 mbar
9881313	HCL6-60-Y	Large diameter hose 3/8", yellow, 60"/150 cm 2x 3/8" SAE female
9881269	CL-60-Y	Charging hose, yellow, 1/4" SAE, 60"/150 cm 1x straight 1/4" SAE, 1x bended 1/4" SAE with core depressor