Acknowledged globally





# REFVAC-RC

#### Item Number 4688541

The REFVAC-RC is the optimal device for checking the evacuation process on the construction site or in the laboratory. The device scores with its high accuracy and communicates wirelessly with the REFMESH<sup>TM</sup> App and the REFMATE<sup>TM</sup>, so that long-term measurements are possible with it. With the help of the REFMESH<sup>TM</sup>, all measured values are compiled in a detailed report.

- Integrated display
- High precision
- High resolution in low vacuum
- Wireless communication
- Signal range 328 ft.
- Intuitive handling
- Flexible power supply with USB

## **Technical Data**

Material	Brass   ABS   Polycarbonate   FR-4	
Colour	yellow (RAL 1023)   green (RAL 6026)	
Standards	CE / FCC / IC / RCM / RoHS / REACH	
RoHS Conformity	Yes	
Working Pressure	30 bar	
Gas Connection	1/4" SAE	
Pressure Scale	Pa   Torr   inHg   mTorr   mbar   micron   psi	
Pressure Range	atm - 0 micron	
Resolution	0.1 micron	
Battery	3 x AAA   Alternative Power Supply USB Mirco-B	
Operating Hours	> 100	

Acknowledged globally



Pressure Type	Absolute Pressure	
Scope of Supply	Batteries   Pouch   Quick Guide   Calibration Certificate   Filter	
Packaging	Blister	
Sensor Type	Pirani Sensor	
Accuracy	±5% of reading or ±10micron: From 10 to 10'000 micron	
	±10% of reading: From 10'000 to 30'000 micron	
	Indication: From 30'000 micron to atm	

#### Accessories

4687845	REFVAC-T	Forged female flare branch tee connection: $3 \times 1/4$ " SAE, with O-ring
4687631	SWIVEL-ARM- 1/4"SAE-N	Swivel arm for vacuum gauge, 1/4" SAE
4688477	VCL-60- 3/8"SAEx1/4"SAE	Vacuum hose 3/8" SAE x 1/4" SAE, 60"/150cm
4687701	32525	Valve core replacing tool, 1/4"SAE
4687740	32525-5/16"SAE	Valve core replacing tool, 5/16"SAE
4503635	EZ-125/12	Sealant, 12 pieces per package

## **Spare Parts**

4688566	REFVAC-FILTER/5	Replacement filter for REFVAC-RC, 5 pieces
4676110	NFT5-4-K-GREEN	Seal flare cap 1/4" SAE